

Highlights:

- Stores up to 42 units of 19" Equipment
- Standard keylock for both doors
- Integrated ventilation grid on top
- 50 mm Wheels + leveling feet included
- Removable sides for easy installing & cabling
- Punched square holes for use with snap-in cage nuts
- Front and rear in depth adjustable 19" profiles (max 740 mm)
- Tempered glass door with keylock
- Reversible door position

Product information:

The SPR842 is a professional 19" rack compliant to the ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. A cold rolled steel 2 mm thick frame and 1,2 mm thick plates provide a solid and stable construction making it suitable for heavy equipment, storing up to 42 units inside. The SPR842 comes fully assembled including 50 mm wheels for easy moving and adjustable feet for fixing and levelling once correctly positioned. The 19" mounting profile with punched square holes for use with snap-in cage nuts in combination with the printed unit measurement indicators ensure an easy fitting of the equipment. Adjustable 19 " profiles provide great flexibility for installing equipment depending on its depth. Both front and rear doors are fitted with a standard key lock.



Product Features:

| | | |
|---|----------|--|
| Unit height | | 42 HE |
| Weight | | 220.46 lb |
| Dimensions | | 23.62 x 78.15 (80.91) x 31.50 " (W x H (incl. feet) x D) |
| Max. usable depth | | 29.13 " |
| Wheel | Diameter | 1.97 " |
| Colours | | Black (RAL9004) |
| Accessories | Included | 4 x Key for sidepanel lock |
| | | 1 x Allen key |
| | | 4 x Levelling feet |
| | | 4 x Key for front/back door |
| | | 20 x KS600 |
| | | 20 x KM600 |
| | Optional | KS600 - M6 x 16 mm bolt DIN7985 Black |
| | | KM600 - M6 Cage nuts |
| | | SPR10CS - Rack interconnection slot |
| | | SPR80LR - L-Rail pair |
| | | SPR80FS - Fixed shelf |
| | | SPR80SS - Sliding shelf |
| | | SPR80PT - Rack plinth |
| | | SPR80RF - Cooling roof fan unit (230V) |
| Static load capacity (adjustable feet) | | 1763.70 lb |
| Dynamic load capacity (transport castors) | | 881.85 lb |

Architects' and Engineers' Specifications:

The rack shall have the following dimensions: Height 1985 mm, Depth 800 mm, Width 600 mm, have a Weight of 98 kg and hold up to 42 units. The rack shall comply with ANSI/EIA RS-310D, DIN41491 and IEC60297 standards. 50 mm wheels will be included as well as levelling feet. The frame of the rack shall be constructed out of cold rolled steel of 2 mm thick while for the other parts a thickness of 1.2 mm shall be used. These parts shall have a textured black powder coating (RAL9004) colour. The mounting rail shall be adjustable in depth on the front and rear side and have unit measurement indicators on the front side. Rack shall include tempered smokey grey glass door on the front side and a steel door on the rear side, both equipped with standard key-lock. Sides of the rack shall be removable and the top shall have a ventilation grid.

